

Industrial Range

MODEL

BGP70



Pneumatic
Dead-Weight
Testers.

Primary standards
for Pressure
Calibration

- ▶ Ranges from 1 to 70 bar
- ▶ Standard Accuracy to 0.015%

- ▶ Class 'A' Accuracy to 0.006%
- ▶ Supplied with integral pressure controls



Budenberg

Industrial Range

MODEL

BGP70

Pneumatic Dead-Weight Testers.

Primary standards for Pressure Calibration

Standard Accuracy to 0.015%
Class A with UKAS

Calibration Certificate 0.006%

RANGES:

Bar 1 to 70

kPa 100 to 7000

lb/in² 10 to 1000

kg/cm² 1 to 70

The **BGP base** can be used with any BGP series pistons, allowing testing from 15 mbar to 120 bar. The base requires a supply of Gas slightly above the test pressure, and has precision inlet/outlet valves and a screwpress to enable easy regulation and adjustment of pressure.

The BGP70 is an oil lubricated gas operated piston cylinder unit.

The design uses a 1/16in² hardened and stabilised tool steel piston/cylinder. If required an inert fluid (such as Fomblin) can be used instead of the oil to provide lubrication without contamination of Gas with hydrocarbon vapour. (Consult Budenberg for more details).



ACCURACY

All certificates issued for Budenberg Dead-weight Testers are fully traceable to national standards via equipment with UKAS calibration certificates. A standard accuracy of 0.015% is achieved from 10% of range using supplied corrections to compensate for the effects of gravity, temperature and the actual area of piston unit. Standard accuracy without any corrections for actual area is 0.02% from 1 to 12 bar. Higher accuracy Class A testers are available (supplied with UKAS Calibration certificates for area and mass) allowing an accuracy of 0.006% to be achieved.

WEIGHTS SUPPLIED

+ includes making-up weight or

screw 1 to 70 bar

1 to 70 kg/cm²

Piston +	1
2 wts	1
1 wt	18
2 wts	20
2 wts	4
1 wt	2
1 wt	0.5

100 to 7000 kPa

Piston +	100
2 wts	100
1 wt	1800
2 wts	2000
2 wts	400
1 wt	200
1 wt	50

10 to 1000 lb/in²

Piston	10
2 wts	10
1 wt	180
3 wts	200
1 wt	100
2 wts	40
1 wt	20
1 wt	5

Optional fine increment weights

1 wts	0.4
1 wt	0.2
1 wt	0.1
2 wts	0.04
1 wt	0.02

1 wt	40
1 wt	20
1 wt	10
2 wts	4
1 wt	2

1 wt	4
1 wt	2
1 wt	1
2 wts	0.4
1 wt	0.2

ACCESSORIES

There are many accessories which can be supplied for use with the Dead-weight testers. These include liquid / liquid seals, two gauge stands and many others. Budenberg have extensive experience in the use of Dead-weight testers and can supply accessories for many applications. A separate data sheet of accessories is available.

PACKING DETAILS

1 carton containing base, tool roll and piston unit:
59 x 49 x 38cm. 0.110m³, Nett 20kg, Gross 22kg.
2 x cartons containing weights:
32 x 32 x 31cm. 0.04m³, Nett 25kg, Gross 30kg. ea

SPARES, REPAIR AND RE-CERTIFICATION

Comprehensive service and calibration capability of both Budenberg and non Budenberg test equipment:

Dead-weight Testers (working service or full overhaul).

Portable calibrators (Budenberg & non- Budenberg).

Comparators.

All accuracy ranges can be supplied with UKAS Calibration Certificates.

Certification traceable to national standards.

Rapid turn-around times and hire items available as a temporary replacement for strategically important plant.

**For further information on Accessories, Repairs & Recertification
contact Budenberg and ask for a Data sheet.**



Budenberg Gauge Co. Ltd.

Unit B2 Stuart Road
Altrincham Business Park,
Altrincham WA14 5GJ

Tel: +44 161 777 7300.
Email: sales@budenberg.co.uk

Budenberg Gauge Pvt. Ltd.

299-300, IInd Main Road,
Nehru Nagar,
Old Mahabalipuram Road (OMR),
Chennai - 600 096,
Tamil Nadu , India

Tel : +91 44 24541074
Tel/Fax: +91 44 24541075
Email: sales@budenberg-gauge.in

Budenberg Gauge Asia
Pacific Ltd

Unit 109 Cheung Fat Ind Bldg
64-76 Larch St Tai Kok Tsui
Kln
Hong Kong

Tel : +852 3709 0020
Email: sales@budenberg-gauge.asia

Budenberg Middle East LLC

PO Box 18980
Dubai
United Arab Emirates

Tel: +971 4 2511670
Email: sales@bme-me.com